





CEILING RADIATION DAMPER STANDARD SIDE-OUTLET BOOT FOR REGISTER BOX ASM.

MODEL:
CRD-50-95-BT
CRD-50-EA-95-BT



APPLICATION

CRD-50-95-BT /CRD-50-EA-95-BT is an 3-Hour rated damper, 90° boot, and round collar assembly for 1-Hour rated partitions. The damper is UL fire rated Ceiling/Floor and Ceiling/Roof Assembly L-558, L562, L563, L574, L585, P533, P544, P545 and P547.



CEILING RADIATION DAMPER (UL 3-HOUR RATING)

- Fusible Link (165°F standard) (optional temperatures available-212°F)
- Damper blades 22 gauge galvanized steel
- Roll formed frame 22 gauge galvanized steel
- Ceramic fiber with fiberglass cover (sizes over 80 SQ/IN)
- Rectangular W x H provided actual size for register installation

BOOT/ REGISTER BOX


- 30 Gauge galvanized steel
- Standard 1/2" deep plaster flange (additional depths are available)
- Standard 1" wide flanges (4) sides
- Round type "CR" collar. (provide nominal size)

FIBERGLASS INSULATION

- Exterior wrapped foil faced fiberglass R-6 insulation-Field installed
- 1-1/2" wide UL 181 aluminum duct tape

SIZE UNITS

- Maximum square 12"W x 12"H
- Maximum rectangle 144 SQ/IN



INSTALLATION INSTRUCTIONS
AND THE PRODUCTS SPECIFIED, ARE
IN CONFORMANCE TO ALL OF
UNDERWRITERS LABORATORIES
REQUIREMENTS 555C